


Order-No. 754/10500

Tandem-Platform trailer, for the transport of scaffolds

Weights	total weight thereof tongue weight maximum payload in standard model approx. empty weight approx.	10500 500 8200 2300	kg kg
Measures	loading area inside approx. (length x width) side height loading height empty approx. drawbar length approx coupling height empty approx. total measures length x width approx.		mm mm mm
Tyres:	size	235/75 R 17,5	4-times



Axles:	Fast-running BPW axles with S-cam brakes, maintenance-free parabolic spring assembly and weight adjustment
Brakes:	Pressure air brake EBS (24V) with TEM (automatic park brake), testing sockets, connection hoses with mix-up safe couplings and spring-loaded brakes
Drawbar:	Drawbar made of hot-manufactured steel shade of quality S355, continuously adjustable with a winch, with a truck drawbar eye (40mm), adjustable in the height from approx. 0,72cm up to 1,02m
Chassis frame:	Sturdily electro welded steel construction made of steel shades (IPE steel shapes quality S355 and ULP steel shapes)
Upper body:	Sidewalls laser welded; front wall fixed, sidewalls are swingable and removable; back wall as a tailgate; fixed rear posts; lashing hooks with 3000 daN embedded and disappearing in the side profiles approx. each 60cm; floor made of 24mm strong film coated plywood
Support:	Adjustable support wheel in front with load and fast gear
Electric:	Splash water resistant lighting according to ECE-directive ECE-R 48.03 (Multi-chamber light, attached on the steel frame, LED -position- and marker lights sideways); 24 voltage, 7+7 - or 15-pole depending on customer's request
Varnishing:	Steel parts are steelgrain-blasted, pretreatment with iron phosphate; corrosion blocking zinc phosphate-base coat, electro statically primed and varnished in Acryl-RAL customer chosen colour (High-Solid), then cavity sealing with conserving wax
Accessories:	Two brake shoes with support; contour marking reg. ECE R 104



Order-No. 754/10500

Tandem-Platform trailer, for the transport of scaffolds

Component	Order-No.	Description	€
		Standard model	I
	754/10500	Tandem-Platform trailer	17.190,0
		Accessories	
Upgrading	G00-754	Upgrade to 11.000kg total weight with 1000kg supportive load (payload then about 8700kg)	100,0
	V00-010	with COC/EC type approval: with side protection and clearpasses	400,0
Loading dimensions	Z00-754	Loading area extension for 50cm	443,0
Tyres	Z01-080	Spare tyre 235/75 R 17,5	380,0
	Z01-170	Spare tyre holder underneath the loading area	360,0
	Z01-150	Spare tyre holder attached to the front wall	148,0
Axles	Z02-050	Air suspension with lifting and lowering	2.350,0
Brakes	Z03-150	Duomatic-coupling	68,0
	Z03-181	EBS with 12V instead of 24V	105,0
	Z03-900	Infocenter and diagnosis tool, mounted to the trailer. Gives information about service	475,0
		intervals, running performance etc.	
	Z03-200	Test connection socket for air brake system (right direction)	180,0
Drawbar	Z04-205	Drawbar eye 50mm instead of 40mm	80,0
	Z04-040	Rotary head with alternatively 40mm and 50mm drawbar eyes (not with COC)	1.590,0
Upper body	Z05-045	PVC-guard at the back and the sides (protection against loading fork lifts)	212,0
	Z05-135	1 pair of stanchions about 1m high, can be plugged into the floor	284,
	Z05-122	Rear corner posts removable	124,
	Z05-130	1 pair of locking devices for container embedded in the trailer bottom	370,
	Z05-4xx	various tool boxes – "Accessories for load securing"	extra she
	Z05-015	Surcharge for double door instead of tailgate	540,
	Z05-030	Divided Sidewalls, pluggable middle stakes with steel side walls (necessary with a length of 5,50m)	420,0
	Z05-034	Divided Sidewalls, pluggable middle stakes with varnished aluminium side walls	610,
	Z05-180	Varnished aluminium side walls 40cm high instead of steel side walls – price per m	32,
	Z05-185	Anodized aluminium side walls 40cm high instead of steel side walls – price per m	32,
	Z05-181	Varnished aluminium side walls 60cm high instead of steel side walls – price per m (attention: sidewalls tip to the curbs when lowering!)	69,
	Z05-186	Varnished aluminium side walls 60cm high instead of steel side walls – price per m (attention: sidewalls tip to the curbs when lowering!)	69,
	Z05-189	Folding foot lever galvanized at the back	85,0
	Z05-190	Reduced price for missing walls (front, side, back walls)	-750,
	Z05-670	Net hooks, applicated approx. every 40cm at the sites of the trailer; in order to fit a covering net for load securing	243,
	Z05-710	Elevation of the front wall about 1,50m high, made of mesh, with strengthening	625,
	Z05-715	Elevation of the front wall about 1m high made of aluminium side walls with strengthening	600,
	Z05-720	2 supports at the back with securing	264,
	Z05-850	Top frame for tarpaulin, 5,00 x 2,45 x 2,60m	on reque
	Z05-861	Tarpaulin made of PVC with rear blind for top frame Z05-852, colour to your wish	on reque
	Z05-972	C-rails embedded in the floor	on reque
	Z05-930	for Export: sideprotection made of an aluminium-profile 100mm high in front of the wheels	243,
	Z05-935	for Export: mudflaps at the fenders (single tyres) 450x650mm	84,
	Z05-936	for Export: Clear passes inbetween axles (1 pair) more accessories for load securing can you see on an extra price sheet	211,
Varnishing		Chassis frame and front wall galvanized instead of varnished, all non-galvanized parts as	
		axles, drawbar etc are varnished in RAL 9006 white aluminium, sidewalls and ramps	
		varnished in the RAL colour of your choice,	
	Z08-163	length of the trailer: 5,00m – net price	Net 800,
	Z08-164	length of the trailer: 5,50m – net price	Net 990,
	Z08-165	length of the trailer: 6,00m – net price	Net 1120,

Please inquire for special measures!

Prices plus VAT

Delivery ex works. Technical changes subject to alteration. NOTE: Additional Equipment changes empty weight and max. load. Dated: 11/2019