

Your trailer – custom-made

Blomenröhr
Your innovative trailer manufacture



Platform Trailers

	745/5000	752/8900	755/11900	756/14000
Total weight	5000	8900	11900	14000
Payload in kg approx.	3500	6950	9600	11500
Loading area in mm	4000x2300	5000x2450	5000x2450	5000x2450
Loading height unloaded in mmm	780	870	900	1000
Height adjusting range	0,72-1,02m	0,72-1,02m	0,72-1,02m	0,72-1,02m
Floorthickness	18mm	18mm	24mm	24mm
Brake system	ABS	ABS	EBS	EBS

➔ **The plus of Blomenröhr-Platform trailers – this is why they are more stable:**

- ➊ Axles of the brands Hersteller Knott, GFA, BPW o. Gigant with payload reserves
- ➋ Chassis: sturdy welded construction made of profiled steel, all components electrically welded
- ➌ High quality plywood floor, weatherproof glued, 18mm o. 24mm strong
- ➍ Laser welded steel steel sidewalls or sidewalls made of aluminium in different heights
- ➎ Easy load securing: side profile with retractable lashing hooks at a distance of 60cm or with double pattern holes at a distance of approx 20cm with each 2000daN lashing capacity
- ➏ Telescopic support legs with spring bolt as securing (optional)
- ➐ LED-track, position- and marker lights (above 8,9t)
- ➑ Rear flap
- ➒ Rear posts removable (optional)
- ➓ Support winch with high payload (12t) from model 752/8900, model 745/5000 mit support wheel
- ➔ Drawbar with winch, continuously height adjustable
- ➕ Hinges welded to side profile
- ➖ PVC-forklift collision protection (optional)

All models available with COC /EC-type approval!



Serial equipment



500mm high aluminium sidewalls, divided, with front elevation up to 2m height, with warning package (lighted warning signs, connector for rotating beacon), twist locks, air suspension



Model 745/5000: with support wheel, steel sidewalls, net hooks, warning signs, holder for traffic cones, divided sidewalls



Chassis hot-dip galvanized, outer profile with double hole pattern, aluminum side walls 400mm high, elevated front wall made of corrugated mesh, steel plate floor



Central lashing rail with rotatable lashing troughs, 4000 daN load capacity



Stanchions can be plugged in at specified the position, with steel side walls on the front half of the loading area



Hot-dip galvanized chassis, increased steel front wall to 80 cm, stakes can be plugged in at the desired position, additional LED reversing lights, divided side walls

as well as without photo: different loading dimensions, net hooks, anodised side walls, additional lashing troughs, spare wheel and bracket, Duomatic coupling, tarpaulin frame, swivel eyelet (40/50mm towing eyelet) and much more.



With plug-in stanchions on the side, tool box and front wall elevation made of corrugated wire mesh



With sliding tarpaulin body, front wall made of aluminum profiles, warning package (extendable, illuminated warning signs)



As a platform trailer for container transport with telescopic container locks and warning package (extendable, illuminated warning signs, connector for rotating beacon)

Platform version

Blomenröhr Fahrzeugbau GmbH
Schneidweg 31
59590 Geseke | Germany
Tel. +49 2942 57997-70
Fax +49 2942 57997-77
info@blomenroehr.com
www.blomenroehr.com

